

POPULAR OPTIONS



CARHAULERS & BOBCATS

Couplers



C07 - Coupler 2-5/16" Adjustable 4 Hole



C08 - Coupler 2-5/16" Adjustable Hyd.



C09 - Coupler 2-5/16" Adjustable Flat Mount Turtle



C11 - Pintle Ring 3" Adjustable



C14 - Gooseneck Coupler 2-5/16" Adjustable Rd.

Rear Gates



G03 - 3' Fold Gate Tubing w/Exp. Metal



G05 - 4' Split Fold Gate Tubing w/Exp. Metal on 60"



G06 - 4' HD Fold Gate w/Spring Assist



G08 - 5' HD Fold Gate w/Ramp & Springs



G11 - 6' HD Fold Gate Split w/Ramp & Springs

Fenders



F03 - Smooth Plate Tear Drop Fenders (weld-on)



F05 - Diamond Plate Fenders (weld-on)



F08 - Diamond Plate Alum. Tear Drop Fenders (removable)



F09 - Drive-Over Fenders 10" (weld-on)



F06 - Diamond Plate Fenders (removable)

Ramps & Dove Tails



H02 - Slide-IN Ramps 5' x 13" (carhauler)



H03 - Fold Up Ramps 5' x 16" (carhauler)



H08 - Multi Purpose Equipment Dove Assy



D01 - 2' Dove Tail



D02 - 2' Diamond Plate On Dove Tail

QUICK REFERENCE

| GVWR | GAWR | Coupler | Chain | Jack | Tire | Wheel |
|--------|-----------------|-------------------------|--------------------------|----------------------|-------------------|------------|
| 7,000 | 3,500 (ea axle) | 2" A-Frame Cast | 7,600 Lb 5/16 X 29 G#30 | Swivel 5,000 Lb | 205/75 R15 Radial | 15" 5-Hole |
| 9,990 | 5,200 (ea axle) | 2 5/16 Adjustable | 12,600 Lb 1/4 x 28 G#70 | Dropleg 7,000 Lb | 225/75 R15 Radial | 15" 6-Hole |
| 14,000 | 7,000 (ea axle) | 2 5/16 Adjustable | 18,800 Lb 5/16 x 28 G#70 | Dropleg 10k Spring | 235/80 R16 Radial | 16" 8-Hole |
| 16,000 | 8,000 (ea axle) | 2 5/16 Adjustable | 18,800 Lb 5/16 x 28 G#70 | Dropleg 10k Spring | 235/85 R16 Radial | 16" 8-Hole |
| 21,000 | 7,000 (ea axle) | 2 5/16 Adjustable (25k) | 18,800 Lb 5/16 x 28 G#70 | 2 Dropleg 10k Spring | 235/80 R16 Radial | 16" 8-Hole |
| 24,000 | 8,000 (ea axle) | 2 5/16 Adjustable (25k) | 18,800 Lb 5/16 x 28 G#70 | 2 Dropleg 10k Spring | 235/80 R16 Radial | 16" 8-Hole |


AUTHORIZED DEALER

Available In:

Gooseneck or Bumper Pull
 G.V.W.R.: 7,000 to 21,000
 Width: 83", 102" and 80"
 Bumper Pull Length: 12' - 26'
 Gooseneck Length: 16' - 40'
 Fender Width: 9" ea. Fender



Available Colors:



Stock photos. Maybe shown with optional equipment.

Standard Features on 7,000 lb G.V.W.R. CH

- 2" A-Frame 7,000 lb. Coupler
- 2-7,600 Lb 5/16 x 29 G#30 Chains
- 5,000 Lb Top Wind Swivel Jack
- 2-3,500 lb. Spring Axles 1 Elec. Brake
- 15" 5-Hole Wheels
- 205/75 R15 Tires
- Multi-Leaf Spring
- 5" Channel Tongue
- 5" Channel Frame
- 2" x 2" x 3/16" Angle Iron Uprights
- 3" Channel Crossmembers
- Treated Wood Floor
- Removable Smooth Plate Fenders
- 16 Ga. 5-Way Double Insulated Harness
- Mechanical and/or Chemical Pretreatment for maximum Paint Adhesion
- DTM Polyurethane Coating System



STANDARD EQUIPMENT

Made in USA



Scan for more details



STANDARD SPECIFICATIONS



AVAILABLE OPTIONS

7,000, 9,990 & 14,000 G.V.W.R.



Stock photo. May be shown with optional equipment.

CH

Standard Features, 7,000 lb (3,500 ea axle) CH

- Coupler:** 2" A-Frame 7,000 lb
- Axles:** 2-3,500 lb Spring Axles 1 Elec. Brake
- Frame:** 5" Channel
- Tongue:** 5" Channel
- Jack:** 5,000 Lb Top Wind Swivel
- Crossmembers:** 3" Channel
- Floor:** Treated Wood
- Lights:** D.O.T. Stop, Tail, Turn and Clearance
- Finish Coat:** DTM Polyurethane Coating System

Length: Weight:*

| | |
|-----------|-----------|
| 83" X 12' | 1,860 Lbs |
| 83" X 14' | 2,004 Lbs |
| 83" X 16' | 2,160 Lbs |
| 83" X 18' | 2,310 Lbs |
| 83" X 20' | 2,462 Lbs |
| 83" X 22' | 2,665 Lbs |

**[Base Weight Estimate Only]*

14,000 G.V.W.R.



GOOSENECK AVAILABLE

CB

Standard Features, 14,000 lb (7,000 ea axle) CB

- Coupler:** 2-5/16" Adjustable
- Axles:** 2-7,000 lb Drop Axles 1 Elec. Brake
- Jack:** 1-10K Spring Loaded Dropleg
- Frame:** 6" I-Beam
- Tongue:** 6" I-Beam
- Top Front Rail:** 2" X 2" X 1/8" Tubing
- Crossmembers:** 3" Channel
- Lights:** D.O.T. Stop, Tail, Turn and Clearance
- Finish Coat:** DTM Polyurethane Coating System

Length: Weight:*

| | |
|-----------|-----------|
| 80" X 16' | 2,743 Lbs |
| 80" X 18' | 2,873 Lbs |
| 80" X 20' | 3,019 Lbs |

**[Base Weight Estimate Only]*

All Gooseneck Carhaulers are Powder Coated

10,400 & 14,000 G.V.W.R.



Stock photo. May be shown with optional equipment.

BC

Standard Features, 9,990 lb (5,200 ea axle) BC

- Coupler:** 2-5/16" Adjustable
- Axles:** 2-5,200 lb Drop Axles 1 Elec. Brake
- Frame:** 4" X 6" Angle Iron
- Tongue:** 6" Channel
- Jack:** 1-10k Dropleg Spring Return
- Crossmembers:** 3" Channel
- Floor:** 1/8" Diamond Plate
- Lights:** D.O.T. Stop, Tail, Turn and Clearance
- Finish Coat:** DTM Polyurethane Coating System

Length: Weight:*

| | |
|-----------|-----------|
| 80" X 12' | 2,695 Lbs |
| 80" X 14' | 2,852 Lbs |
| 80" X 16' | 3,058 Lbs |
| 80" X 18' | 3,256 Lbs |
| 80" X 20' | 3,461 Lbs |

**[Base Weight Estimate Only]*

| Description: | CH | CB | BC | CS |
|---|----|----|----|----|
| Tire Upgrades | | | | |
| ST205/75 R15 LRC 8 Ply. | † | | | † |
| ST225/75 R15 LRD 8 Ply. | • | | | • |
| ST235/80 R16 LRE 10 Ply. | | † | † | |
| ST235/85 R16 LRG 14 Ply. | | • | • | |
| Couplers | | | | |
| Coupler 2" A-Frame Cast | † | | | † |
| Coupler 2" A-Frame Stamped | • | | | • |
| Coupler 2" A-Frame Cast Hyd. | • | | | • |
| Coupler 2" Adjustable | • | | | • |
| Coupler 2-5/16" A-Frame Stamped | • | | | • |
| Coupler 2-5/16" Adjustable | • | † | † | • |
| Coupler 2-5/16" Adjustable Hyd. | | • | • | |
| Coupler 2-5/16" Adjustable Flat Mount Turtle | | | | |
| Pintle Ring 3" Adjustable | • | • | • | |
| Dove Tails | | | | |
| 2' Dove Tail (carhauler) | • | | | • |
| 2' Diamond Plate On Dove Tail | • | | | • |
| 3' Dove Tail (carhauler) | • | | | • |
| 4' Dove Tail (carhauler) | • | | | • |
| Flooring | | | | |
| Steel Floor DP | • | • | † | • |
| Rough Oak Floor | • | • | • | • |
| Douglas Fir Wood Floor | • | • | • | • |
| Fenders | | | | |
| Smooth Plate Tear Drop Fenders (weld-on) | • | | | • |
| Smooth Plate Tear Drop Fenders (removable) | † | | | • |
| Diamond Plate Fenders (weld-on) | • | † | † | † |
| Diamond Plate Fenders (removable) | • | | • | • |
| Diamond Plate Alum. Tear Drop Fenders (removable) | • | | | • |
| Drive-Over Fenders 10" (weld-on) | • | | | • |
| Gates & Ramps | | | | |
| 4' HD Fold Gate w/Spring Assist | • | • | | • |
| 4' HD Split Fold Gate w/Spring Assist | • | • | | • |
| 5' HD Fold Gate w/Ramp & Springs | • | • | | • |
| 5' HD Fold Gate Split w/Ramp & Springs | • | • | | • |
| 6' HD Fold Gate w/Ramp & Springs | • | • | | • |
| 6' HD Fold Gate Split w/Ramp & Springs | • | • | | • |
| 6' Stand Up Ramps w/Center Gate & Springs | | | | |
| 4' Side Fold Gate | | | | |
| Slide-IN Ramps 5' x 13" (carhauler) | † | | | † |
| Fold Up Ramps 5' x 16" (carhauler) | • | • | † | • |
| 3rd. Fold Up Ramp 5' x 16" (carhauler) | • | • | • | • |
| Multi Purpose Equipment Dove Assy | | | | |
| Slide-In Ramps 6' x 13" (carhauler) | | | | |
| Fold Up Ramps 6' x 16" (carhauler) | | | • | |
| 3rd. Fold Up Ramp 6' x 16" (carhauler) | | | • | |
| Crossmembers | | | | |
| 16" Cross-Members | • | • | † | • |
| 12" Cross-Members | • | • | • | • |

[• available option † standard feature]

7,000 G.V.W.R.



Stock photo. May be shown with optional equipment.

CS

Standard Features, 7,000 lb (3,500 ea axle) CS

- Coupler:** 2" A-Frame 7,000 lb
- Axles:** 2-3,500 lb Spring Axles 1 Elec. Brake
- Frame:** 5" Channel
- Tongue:** 5" Channel
- Jack:** 5,000 Lb Top Wind Swivel
- Crossmembers:** 3" Channel
- Floor:** Treated Wood
- Lights:** D.O.T. Stop, Tail, Turn and Clearance
- Finish Coat:** DTM Polyurethane Coating System

Length: Weight:*

| | |
|-----------|-----------|
| 83" X 12' | 2,064 Lbs |
| 83" X 14' | 2,208 Lbs |
| 83" X 16' | 2,364 Lbs |
| 83" X 18' | 2,514 Lbs |
| 83" X 20' | 2,666 Lbs |
| 83" X 22' | 2,869 Lbs |

**[Base Weight Estimate Only]*

| Description: | CH | CB | BC | CS |
|--|----|----|----|----|
| Jacks | | | | |
| Jack Swivel 5000 lb. | † | | | † |
| Jack Drop Leg 7000 lb. | • | | | • |
| Jack Spring Loaded Drop Leg 1-10K | | † | † | |
| Jack Spring Loaded Drop Leg 2-10K (standard on 24'+) | | • | • | |
| Lights | | | | |
| Regular Lights | † | † | † | † |
| LED Lights | • | • | • | • |
| D-Rings | | | | |
| D-Rings 4" Recessed 360 Rotational Bolt On | • | • | • | • |
| D-Rings 3" Weld On (each) | • | • | • | • |
| D-Rings 3" Weld-On (4 Total) | † | † | † | † |
| D-Rings 4" Weld On (each) | • | • | • | • |
| Side Rails | | | | |
| 3" Pipe Top Side Rails (weld on) | | | | † |
| 3" Pipe Top Side Rails (removable) | | | | • |
| 2-3/8" Pipe Top Side Rails (weld on) | | | | • |
| 2-3/8" Pipe Top Side Rails (removable) | | | | • |
| Sq. Tube Side Rails (weld on) | | | | • |
| Sq. Tube Side Rails (removable) | | | | • |
| Exp. Metal Sides 16", 24", 36" & 48" | | | | • |
| Solid Metal On Sides 16", 24", 36" & 48" | | | | • |
| Additional Options | | | | |
| Running Boards | • | | † | • |
| Rub Rail | • | | • | • |
| Fork Holders | • | • | | • |
| 2 - Rear Support Stands (5K Jacks) | • | • | | • |
| 2 - Rear Support Stands (Tube) | • | • | | • |
| 4' Front Stone Guard | • | | | • |
| 4 - Additional Stake Pockets | • | | • | • |
| Front Tongue Mount Tool Box | • | • | † | • |
| Spare Tire & Mount | • | • | • | • |
| Winch Plate | • | • | • | • |
| Winch 12 Volt (15000lb) | • | • | • | • |
| Zinc Primer | • | • | • | • |
| Axle Options | | | | |
| 2 - 3,500 Lb Axles (1 Elec Brake) | † | | | † |
| 2 - 3,500 Lb Axles (2 Elec Brakes) | • | | | • |
| 2 - 5,200 Lb Axles (1 Elec Brake) | • | | † | • |
| 2 - 5,200 Lb Axles (2 Elec Brakes) | • | | • | • |
| 2 - 7,000 Lb Axles (1 Elec Brake) | • | † | • | • |
| 2 - 7,000 Lb Axles (2 Elec Brakes) | • | • | • | • |
| 3 - 7,000 Lb Axles (3 Elec Brakes) | • | • | • | • |

Axles Available in Drop and Torsion, Spring is Standard