

POPULAR OPTIONS



UTILITIES & LANDSCAPES

Rear Gates



G03 - 3' Fold Gate Tubing w/Exp. Metal



G05 - 4' Split Fold Gate Tubing w/Exp. Metal



GF1 - Front Fold Gate



GS1 - 4' Side Fold Gate



GS4 - Side Rail Ramps

Fenders & Sides



F06 - Diamond Plate Fenders (removable)



F04 - Smooth Plate Tear Drop Fenders (removable)



F05 - Diamond Plate Fenders (weld-on)



Q04 - Exp. Metal Sides 36"



R04 - Solid Metal Sides 36"

Couplers & Ramps



C01 - Coupler 2" A-Frame Cast



C06 - Coupler 2-5/16" A-Frame Stamped



C07 - Coupler 2-5/16" Adjustable 4 Hole



H02 - Slide-In Ramps 5' X 13"



H03 - Fold-Up Ramps 5' X 16"

LED Lights, D-Rings & Spare Tire Mount



L03 - Lighting LED



M02 - D-Rings 3" Weld On



M04 - D-Rings 4" Recessed 360 Rotational Bolt On



TM1 - Spare Tire Mount

QUICK REFERENCE

GVWR	GAWR	Coupler	Chain	Jack	Tire	Wheel
7,000	3,500 (ea axle)	2" A-Frame Cast	1/4" w/Safety Latch Hook	5,000 Lb Top Wind	205/75 R15 Radial	15" 5-Hole

AUTHORIZED DEALER



220 FM 2216 • Sumner, Texas 75486

903-783-3900 • www.loadtrail.com

Product information and specifications are subject to change without notice.



Available In:

Bumper Pull Only
 G.V.W.R.: 7,000
 Width: 60" 77" 80" 83" 96" & 102"
 Length: 8' - 23'
 Fender Width: 9" per Fender

Available Colors: Black Grey White Red Blue Green Yellow Orange

Stock photos. May be shown with optional equipment.

Standard Features on 3,500 lb G.V.W.R. UT

- 2" A-Frame 7,000 Lb Coupler
- 7,600 Lb 5/16 x 29 G#30 Chains
- 5,000 Lb Top Wind Swivel Jack
- 2-3,500 Lb Spring Axles 1 Elec. Brake
- 15" X 5" 5-Hole Wheels
- 205/75 R15 Tires
- Multi-Leaf Springs
- Removable Smooth Plate Fenders
- 4" Channel Tongue
- 4" Channel Frame
- 2" X 2" X 3/16" Angle Iron Crossmembers
- 2" X 2" X 1/8" Tubing Uprights
- Removable Side Rails
- 2" X 2" X 1/8" Angle Iron Top Rail
- Treated Wood Floor
- D.O.T. Stop, Tail, Turn, Clearance Lights
- Mechanical and/or Chemical pretreatment for maximum Paint Adhesion, Finish (prep)
- DTM Polyurethane Coating System



LOAD TRAIL • 220 FM 2216 • Sumner, Texas 75486 • 903-783-3900 • www.loadtrail.com

STANDARD SPECIFICATIONS



AVAILABLE OPTIONS

7,000 G.V.W.R.



Stock photo. May be shown with optional equipment.

UT

Standard Features, 7,000 lb G.V.W.R. (3,500 ea axle) UT

- Coupler:** 2" A-Frame 7,000 lb
- Axles:** 2-3,500 lb 1 Elec. Brake (Spring)
- Frame:** 4" Channel
- Tongue:** 4" Channel
- Side Rails:** 2" X 2" Angle Iron (removable)
- Crossmembers:** 2" X 2" X 3/16" Angle Iron
- Floor:** Treated Wood
- Lights:** D.O.T. Stop, Tail, Turn and Clearance
- Finish Coat:** DTM Polyurethane Coating

Additional Widths Available

Length:	Weight:*
83" X 10'	1,405 lbs
83" X 12'	1,545 lbs
83" X 14'	1,676 lbs
83" X 16'	1,823 lbs
83" X 18'	1,966 lbs
83" X 20'	2,111 lbs

*[Base Weight Estimate Only]

7,000 G.V.W.R.



Stock photo. May be shown with optional equipment.

LT

Standard Features, 7,000 lb G.V.W.R. (3,500 ea axle) LT

- Coupler:** 2" A-Frame 7,000 lb
- Axles:** 2-3,500 lb 1 Elec. Brake (Spring)
- Frame:** 4" Channel
- Tongue:** 4" Channel
- Side Rails:** 2' Mesh Sides (Removable)
- Crossmembers:** 2" X 2" X 3/16" Angle Iron
- Floor:** Treated Wood
- Lights:** D.O.T. Stop, Tail, Turn and Clearance
- Finish Coat:** DTM Polyurethane Coating

Additional Widths Available

Length:	Weight:*
83" X 10'	1,688 lbs
83" X 12'	1,823 lbs
83" X 14'	1,986 lbs
83" X 16'	2,142 lbs
83" X 18'	2,271 lbs
83" X 20'	2,461 lbs

*[Base Weight Estimate Only]

7,000 G.V.W.R.



Stock photo. May be shown with optional equipment.

TV

Standard Features, 7,000 lb G.V.W.R. (3,500 ea axle) TV

- Coupler:** 2-5/16" Adjustable
- Axles:** 2-3,500 lb 1 Elec. Brake (Spring)
- Frame:** 4" Channel
- Tongue:** 4" Channel
- Jack:** 5,000 lb Top Wind Swivel
- Crossmembers:** 2" X 2" X 3/16" Angle Iron
- Floor:** Treated Wood
- Lights:** D.O.T. Stop, Tail, Turn and Clearance
- Finish Coat:** DTM Polyurethane Coating

Description:	UT	LT	TV	UE
Tire Upgrades				
ST205/75 R15 LRC 8 Ply.	†	†	†	†
ST225/75 R15 LRD 8 Ply.	•	•	•	•
Couplers				
Coupler 2" A-Frame Cast	†	†		•
Coupler 2" A-Frame Stamped	•	•		†
Coupler 2" A-Frame Cast Hyd.	•	•		•
Coupler 2" Adjustable 4 Hole	•	•		•
Coupler 2-5/16" A-Frame Stamped	•	•		
Coupler 2-5/16" Adjustable 4 Hole	•	•	†	
Dove Tails & Floors				
2', 3' & 4' Dove Tails	•	•		•
Steel Floor DP	•	•		•
Mesh Floor	•	•		•
Rough Oak Floor	•	•	•	•
No Floor On Deck	•	•		•
Douglas Fir Wood Floor	•	•	•	•
Fenders				
Smooth Plate Tear Drop Fenders (weld-on)	•	•		†
Smooth Plate Tear Drop Fenders (removable)	†	†		
Diamond Plate Fenders (weld-on)	•	•		•
Diamond Plate Fenders (removable)	•	•		
Diamond Plate Alum. Tear Drop Fenders (removable)	•	•		
Gates & Ramps				
Rear Tail Gate (even with sides)	•			
3' Fold Gate Tubing w/Exp. Metal	•	•		
3' Fold Gate Angle Iron w/Exp. Metal				•
4' Fold Gate Tubing w/Exp. Metal	•	†		
4' Fold Gate Angle Iron w/Exp. Metal				•
4' Split Fold Gate Tubing w/Exp. Metal	•	•		
4' Split Fold Gate Angle Iron w/Exp. Metal				•
5' HD Fold Gate w/Ramp & Springs	•	•		
5' HD Fold Gate Split w/Ramp & Springs	•	•		
4' Fold In Gate Tubing w/Exp. Metal	•			•
4' Fold In Gate Angle Iron w/Exp. Metal				•
4' HD Fold Gate w/Ramp & Springs	•	•		
4' HD Split Fold Gate w/Ramp & Springs	•	•		
4' Bi-Fold Gate w/Exp. Metal	•	•		•
Front Fold Gate	•	•		•
4', 5' & 6' Side Fold Gate	•	•		•
Side Rail Ramps				
Slide-IN Ramps 5' x 13"	•	•		
Slide In Ramps 18" X 60"				†
Fold Up Ramps 5' x 16" (carhauler)	•	•		
13" X 60" Angle Iron Slide-In Ramps				•
Snow Mobile Slide In Ramps 59" X 72"			•	
Crossmembers				
16" Cross-Members	•	•	•	•

[• available option † standard feature]

Description:	UT	LT	TV	UE
Jacks				
Jack A-Frame 2000 lb.				†
Jack Swivel 5000 lb.	†	†		•
Jack Drop Leg 7000 lb.	•	•		•
Lights				
Regular Lights	†	†	†	†
LED Lights	•	•	•	•
D-Rings				
D-Rings 4" Recessed 360 Rotational Bolt On	•	•	•	•
D-Rings 3" Weld On (each)	•	•	•	•
D-Rings 4" Weld On (each)	•	•	•	•
Side Rails				
Angle Iron Side Rails (weld on)	•	•		†
2-3/8" Pipe Top Side Rails (weld on)	•	•		•
Sq. Tube Side Rails (weld on)	•	•		•
Angle Iron Side Rails (removable)	†	†		
2-3/8" Pipe Top Side Rails (removable)	•	•		
Sq. Tube Side Rails (removable)	•	•		
Rail Pipe Over Top Rail	•	•		
Rail Tube Over Top Rail	•	•		
Exp. Metal Sides 14"	•			
Solid Metal Sides 14"	•			
Exp. Metal Sides 24"				†
Solid Metal Sides 24"				•
Exp. Metal Sides 36" & 48"				•
Solid Metal Sides 36" & 48"				•
Additional Options				
Running Boards	•	•		
Rub Rail				•
Rear Support Stands (2 - 5,000 Lb Swivel Jacks)	•	•	•	•
Rear Support Stands (Tube)	•	•	•	
Spring Assist on Fold Gates	•	•		•
Diamond Plate Front Stone Guard	•	•		•
4 - Additional Stake Pockets	•	•	•	•
Front Tongue Mount Tool Box	•	•	•	•
Front Tool Cage	•	•	•	•
Front Tool Cage 2' X 4' W/side Doors	•	•	•	•
Spare Tire & Mount	•	•	•	•
Zinc Primer	•	•	•	•
Axle Options				
2 - 3,500 Lb Axles (1 Elec Brake)	†	†	†	†
2 - 3,500 Lb Axles (2 Elec Brakes)	•	•	•	•
2 - 3,500 Lb Drop Axles (1 Elec Brake)	•	•		
2 - 3,500 Lb Drop Axles (2 Elec Brakes)	•	•		
2 - 3,500 Lb Tors Axles (1 Elec Brake)	•	•		
2 - 3,500 Lb Tors Axles (2 Elec Brakes)	•	•		

7,000 G.V.W.R.



Stock photo. May be shown with optional equipment.

UE

Standard Features, 7,000 lb G.V.W.R. (3,500 ea axle) UE

- Coupler:** 2" A-Frame 5,000 lb Stamped
- Axles:** 2-3,500 lb 1 Elec. Brake (Spring)
- Frame:** 2" X 3" X 3/16" Angle Iron
- Tongue:** 4" Channel
- Side Rails:** 2" X 2" Angle Iron (weld-on)
- Crossmembers:** 2" X 2" X 3/16" Angle Iron
- Floor:** Treated Wood
- Lights:** D.O.T. Stop, Tail, Turn and Clearance
- Finish Coat:** DTM Polyurethane Coating

Additional Widths Available

Length:	Weight:*
83" X 10'	1,227 lbs
83" X 12'	1,359 lbs
83" X 14'	1,479 lbs
83" X 16'	1,615 lbs
83" X 18'	1,716 lbs

*[Base Weight Estimate Only]